

## Drive

Remove deposits and open lateral connections after lining in small mains from 6" to 16".

## Drive+

Get fast and reliable descaling and reinstatement in sewer mains up to 24". The Drive+ may be equipped with two differently-sized air motors.

### Specs

Line size	6" to 16"	6" to 24"
Self Propelled Carriage		
Dimensions	approx. 45" L x 7.5" W x 7" H Outer diameter: 4.72"	approx. 42" L x 7.5" W x 7" H Outer diameter: 5.31"
Weight	approx. 46 lbs	approx. 77 lbs
Cable Drum	Manual cable drums with pneumatic/electrical rotary transmissions and manual brakes	
Hose Length	328 ft or 492 ft	328 ft or 492 ft
Weight	328 ft hose: approx. 194 lbs 492 ft hose: approx. 230 lbs	328 ft hose: approx. 353 lbs 492 ft hose: approx. 397 lbs
Camera	Integrated color camera with LED illumination	Swivel head camera with LED illumination
Control	Removable control unit with 2 joysticks in protective case and tablet	7 inch universal control unit

### Features

- 400° electrically driven rotation
- Approx. 90° swivel movement
- Pneumatic stabilization for improved traction
- Permanent internal nitrogen pressure monitoring
- Accessories case
- Reverse-driving sensor
- Many additional options



- 400° electrically driven cutting arm rotation
- Approx. 90° swivel movement, add'l movement cutting motor
- 2 exchangeable air driven cutting motors
- Pneumatic stabilization for improved traction
- Permanent internal nitrogen pressure monitoring
- Different wheel sets
- Integrated positioning sensors
- Accessories case
- Reverse-driving sensor
- Many additional options



033026